



MATERIAL SAFETY DATA SHEET

1200 Mastic (Water-Based)

1. Product And Company Identification

Supplier

Mar-flex Waterproofing & Building Products
500 Business Parkway
Carlisle, OH 45005 USA

Telephone Number: 513-422-7285
FAX Number: 513-422-7282
E-Mail: info@mar-flex.com
Web Site: www.mar-flex.com

Manufacturer

Mar-flex Waterproofing & Building Products
500 Business Parkway
Carlisle, OH 45005 USA

Telephone Number: 513-422-7285
FAX Number: 513-422-7282
E-Mail: info@mar-flex.com
Web Site: www.mar-flex.com

Supplier Emergency Contacts & Phone Number

Chem-Trec: 1-800-424-9300

Manufacturer Emergency Contacts & Phone Number

Chem-Trec: 1-800-424-9300

Issue Date: 12/21/2011

Product Name: 1200 Mastic (Water-Based)
Chemical Name: Hybrid Latex Emulsion
CAS Number: Not Established
MSDS Number: 149
Product Code: CWMA-12105

Product/Material Uses - For use in conjunction with the 1200 VP Air Barrier membrane to fill any cracks or voids in the masonry that will be receiving the membrane.

Product Identification Text - 5 Gallon Buckets

2. Composition/Information On Ingredients

This products hazardous ingredients, when evaluated by criteria established in the OSHA Hazard Communication Standard (29 CFR 1910.1200), are present at less than 1%.

EMERGENCY OVERVIEW

Deliberate or direct ingestion of vapor or spray or mist may be harmful or fatal.

3. Hazards Identification

Primary Routes(s) Of Entry - Eyes, Skin, Inhalation & Ingestion

Eye Hazards - Causes eye irritation.

Skin Hazards - Causes skin irritation, rash.

Ingestion Hazards - May cause gastric disturbance.

Inhalation Hazards - May cause irritation to respiratory tract.

Chronic/Carcinogenicity Effects - May cause Dermatitis. Skin sensitivity may develop.

Conditions Aggravated By Exposure - Latex sensitivity.

If symptoms or irritation occur with any exposure, call a physician.

First Aid (Pictograms)



4. First Aid Measures

Skin - Wash the affected area under tepid running water using a mild soap. If irritation occurs, seek medical attention.

Inhalation - If affected, move person to fresh air. If breathing is difficult, administer oxygen. If not breathing or if no heartbeat, give artificial respiration or CPR. Immediately call a physician.



MATERIAL SAFETY DATA SHEET

1200 Mastic (Water-Based)

5. Fire Fighting Measures

Flash Point: NA °F

Extinguishing Media - Use CO2 (Carbon Dioxide), dry chemical, water spray or foam.

Fire Fighting Instructions - Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Small Spills: Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Sweep and discard. Avoid runoff to waterways and sewers.

Handling & Storage (Pictograms)



7. Handling And Storage

Storage Precautions - KEEP FROM FREEZING. STORE DRUMS INDOORS, OFF THE FLOOR AT AN AMBIENT TEMPERATURE ABOVE 35 DEGREES F. IF PRODUCT FREEZES, IT WILL NOT BE USABLE AS IT WILL NOT GO BACK TO ITS NATURAL STATE.

Work/Hygienic Practices - Avoid skin contact. Wash hands before eating and smoking.

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

Engineering Controls - Ventilation: Provide sufficient mechanical (general and/or local exhaust).

Eye/Face Protection - Safety glasses with side shields or goggles.

Skin Protection - Wear insulated gloves when handling hot material. To prevent repeated and prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection - NIOSH/MSHA VAPOR AND DUST RESPIRATOR IS REQUIRED.

Other/General Protection - Wash hands before eating or drinking.

9. Physical And Chemical Properties

Appearance - Gray

Odor - Ammonia

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: 212 °F

Specific Gravity: .09 - 1.1

Solubility: Miscible

Evaporation Rate: 1.0

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur



MATERIAL SAFETY DATA SHEET

1200 Mastic (Water-Based)

10. Stability And Reactivity - Continued

Incompatible Materials - Contact with acids or salts will cause coagulation. This is not hazardous.

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Dispose of wastes in an approved waste disposal facility.

14. Transport Information


Freight Class

55

PROTECT FROM FREEZING. PRODUCT WILL FREEZE AT 32 DEGREES F. DO NOT ALLOW TO SIT ON DOCKS. DO NOT SHIP IN AN UNHEATED TRAILER. DO NOT SIT CONTAINERS OF PRODUCT DIRECTLY ON THE FLOOR. PRODUCT DOES NOT FOLLOW A NORMAL FREEZE THAW CYCLE. IF FREEZING OCCURS PRODUCT BECOMES UNUSABLE.

15. Regulatory Information

No Data Available...

NFPA	HMIS								
	<table border="1"><tr><td>HEALTH</td><td>1</td></tr><tr><td>FLAMMABILITY</td><td>0</td></tr><tr><td>REACTIVITY</td><td>0</td></tr><tr><td>PERSONAL PROTECTION</td><td>F</td></tr></table>	HEALTH	1	FLAMMABILITY	0	REACTIVITY	0	PERSONAL PROTECTION	F
HEALTH	1								
FLAMMABILITY	0								
REACTIVITY	0								
PERSONAL PROTECTION	F								

16. Other Information

Revision/Preparer Information

This MSDS Supercedes A Previous MSDS Dated: 04/09/2009

Disclaimer

The above information pertains to this product as currently formulated and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product.

Mar-flex Waterproofing & Building Products makes no warranties, express or implied and assumes no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Mar-flex Building Solutions