



## Marflex 5000™

### Below-grade Exterior Foundation Waterproofing Membranes The ultimate waterproofing protection for your residential walls

Marflex 5000 Waterproofing Membranes are tested and proven membranes that can be applied over almost any clean, dry, sound substrate. Their permanent elasticity allows for movement with the structure. Marflex 5000 membranes will not become brittle, evaporate, or lose their flexibility or waterproofing abilities. They resist freeze-thaw cycles and testing shows that Marflex 5000 membranes outlast conventional protection methods. Marflex 5000 is available in both solvent-based and water-based<sup>1</sup>.

#### Uses

Marflex 5000 membranes are recommended for new construction waterproofing of all below-grade basement walls of poured concrete<sup>2</sup> or unit masonry construction<sup>3</sup>. Marflex 5000 membranes can be used as a spray only or as part of a waterproofing system.

#### Code Compliance

ICC Evaluation Service, Inc. (ICC-ES), has issued evaluation report NER-658 on the Marflex 5000 Waterproofing Membrane. ICC-ES finds that, subject to the conditions set forth in NER-658, the membrane complies with the 2000 *International Building Code*, or is a suitable alternative to what is specified in the code.

#### Two System Components

Marflex allows you to customize your waterproofing system by matching the right coating to the right board.

For drainage plus R-value:

Drain & Dry, QuickSilver or the ShockWave 1 or 2

For more drainage flow with no R-value:

Geo-Mat™ Plus

#### Limited Residential Warranty<sup>4 5 6</sup>

When you build using Marflex 5000 you receive one of the best warranties in the industry.

Choose from the Standard, Bronze, Silver or Gold levels below. Anyway you go Marflex backs every level with the best warranty in the business.

LEVEL	MEMBRANE combined with BOARD gives you WARRANTY		
Standard	Marflex 5000	None	15 Years
Bronze	Marflex 5000	Geo-Mat Plus Drain & Dry ¾" QuickSilver	40 Years
Silver	Marflex 5000	1" Shockwave 1-3/8" QuickSilver	50 Years
Gold	Marflex 5000	2" Shockwave 2-¾" QuickSilver	60 Years

PRODUCT DATA

## Division 7

07140 Fluid Applied Waterproofing

<sup>1</sup> See Water-Based Installation Instructions

<sup>2</sup> See Poured Wall Installation Instructions

<sup>3</sup> See Unit Masonry Installation Instructions

<sup>4</sup> New Construction Only

<sup>5</sup> See Applicator For Availability

<sup>6</sup> For Poured Walls Only



## Marflex 5000™

### Below-grade Exterior Foundation Waterproofing Membranes *The ultimate waterproofing protection for your residential walls*

#### Marflex 5000 Membrane Properties<sup>7</sup>

	Solvent-Based	Water-Based
Color	Black	Black
Total Solids	70-75%	60-70%
Density	7.6 lbs.	7.6 lbs.
Shelf Life	-	6 months
Application Method	Spray	Spray
Application Temp (Ambient)	0° to 150°F	0° to 130°F
Film Thickness	60 mil (dry)	60 mil (dry)
Total Cure Time	24 hrs.	24 hrs.
Adhesion to Concrete	No Adhesion Loss	No Adhesion Loss
Elongation @ 70° F	1725%	1725%
Low Temp Flexibility	-15°F	-15°F
Crack Bridging Ability	10 cycles without bond failure	10 cycles without bond failure
Water Vapor Permeance (40 mil dry coating)	0.12 perm (grains/sq.ft./h)	0.12 perm (grains/sq.ft./h)
Liquid Water Absorption	No Absorption	No Absorption
Mold Growth/Bacterial Attack	No Degradation	No Degradation
Resistance to Hydrostatic Pressure Head	No Water Infiltration	No Water Infiltration
Coverage Rate	3.2 – 4.0 gal./100 ft. <sup>2</sup>	3.3 – 5.0 gal./100 ft. <sup>2</sup>
Tensile Strength	48 p.s.i. min.	48 p.s.i. min.

#### PRODUCT DATA

## Division 7

07140 Fluid Applied Waterproofing

HEALTH AND SAFETY INFORMATION IS GIVEN IN THE MATERIAL SAFETY DATA SHEET AVAILABLE FOR THIS PRODUCT. THE MATERIAL SAFETY DATA SHEET SHOULD BE READ AND UNDERSTOOD BEFORE USING THIS PRODUCT.

Manufactured By:  
Marflex Building Solutions  
6866 Chrisman Lane, Middletown, OH 45042  
(800) 498-1411 | (513) 422-7285 | Fax – (513) 422-7282  
E-mail: [technicalsupport@mar-flex.com](mailto:technicalsupport@mar-flex.com)  
Web-site: [www.MarflexBuildingSolutions.com](http://www.MarflexBuildingSolutions.com)

Rev. 07-09.1

<sup>7</sup> ASTM Methods Available Upon Request