

PRODUCT DESCRIPTION:

362 Mastic is a heavy bodied trowel grade coating.

PURPOSE:

362 Mastic is excellent for patching tie holes, filling in honeycombed areas in both rough and smooth masonry surfaces.

ADVANTAGES:

- Remains flexible during freeze-thaw cycles
- Can be used during any season
- Ready to use

SPECIFICATIONS:

- Color Black
- Consistency Rubber coating
- ASTM D-4586 Type I
- ASTM D-3409

SIZE/PACKAGING:

5 Gallon Bucket

APPROXIMATE USAGE:

Actual coverage rate will vary depending on thickness product is applied.

PREP/APPLICATION:

All surfaces should be free from oil, grease, rust and any other debris. Can be trowel or hand applied over wall ties, honeycombs or any surface flaw.

PREP/APPLICATION:

Remove below grade wall ties inside the basement and out. Patch all outside below grade wall ties with 362 Mastic.

Poured concrete walls must be free of voids and honeycombs. Any such areas, if present, should be covered with the 362 Mastic.

CLEAN UP:

For contact with cold material clean exposed skin with mineral oil, then wash with soap and water.

PRODUCT HANDLING/STORAGE:

- Do not thin
- Do not use near open flames
- Avoid breathing solvent fumes
- Avoid prolonged contact to skin
- Wear rubber gloves
- Keep container closed when not in use. Unlimited shelf life if properly stored.

WARNING/DANGER:

Use with adequate ventilation. Keep out of reach of children. Do not take internally. In case of ingestion, CALL A PHYSICIAN immediately. DO NOT INDUCE VOMITING.

Product Only Warranty:

The information herein is the best available relating to 362 Mastic and the recommendations contained herein are based on tests believed to be reliable.

Marflex Building Solutions warrants the product to be of good quality and manufactured to meet published physical properties and quality control standards and will replace or refund the purchase price of this product if proved defective within one year of date of application. This warranty does not apply if there is no working drainage system.

Except as specifically provided herein, Marflex Building Solutions makes no warranty, express, implied or oral including but not limited to any warranty or merchantability, fitness for a particular purpose, usage of trade, course of dealing or course of performance in connection with this agreement. In no event shall Marflex be liable on any such warranty with respect to the Marflex 362 Mastic. Marflex shall not be liable for incidental or consequential damages including, but not limited to damages of the structure, its replacement, contents or personal injury. Some states do not allow limitations on how long an implied warranty lasts or allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

HEALTH AND SAFETY INFORMATION IS GIVEN IN THE MATERIAL SAFETY DATA SHEET AND THE PRODUCT DATA SHEET AVAILABLE FOR THIS PRODUCT. THESE SHOULD BE READ AND UNDERSTOOD BEFORE USING THIS PRODUCT.

Marflex Building Products 6866 Chrisman Lane, Middletown, OH 45042 (800) 498-1411| (513) 422-7285 | Fax (513) 422-7282 E-mail: <u>technicalsupport@mar-flex.com</u> Web-site: <u>www.MarflexBuildingSolutions.com</u>

Rev. 10-09.1