



Fiberglass Reinforcement Fabric

PRODUCT DESCRIPTION:

The Fiberglass Fabric Reinforcement is a reinforcing fabric composed of highly flexible woven fiberglass yarn.

It is used on the exterior of the control joint from the top of the footer up to the grade line.

PURPOSE:

To protect the Control-Joints created in foundation walls. The Fiberglass Fabric Reinforcement works in conjunction with the Waterstop Elastomeric Sealant and together they create a watertight seal on the outside below-grade that resists hydrostatic pressure.

ADVANTAGES:

- Resistant to rot and water damage
- High tensile strength
- Acid and alkali resistant
- Compatible with asphalt or tar and all accepted waterproofing and coating compounds

SPECIFICATIONS:

ASTM D-1668, Fed. Spec. HH-C466b

- Tensile Strength –
- Warp (lbs./lineal inch) – 75
- Fill (lbs./lineal inch) - 75

PACKAGING:

6" x 150' Rolls

APPROXIMATE USAGE:

One roll - App. 18, 8' Control Joints

PREP/APPLICATION:

Remove the reusable plastic extrusions used to create Control-Joints in the foundation. Follow the instructions for the application of the Waterstop Elastomeric Sealant.

Then press the Fiberglass Reinforcement Fabric into the Waterstop Elastomeric Sealant before curing occurs. It is applied on the exterior of the control joint from the top of the footer to the grade line.

CLEAN UP:

Place all excess fabric into trash.

PRODUCT HANDLING/STORAGE:

- Dispose of all products in an environmentally safe manner.

WARNING/DANGER:

- KEEP OUT OF REACH OF CHILDREN.
- INDUSTRIAL USE ONLY

PRODUCT ONLY WARRANTY:

We warrant the products to be of good quality and manufactured to meet published physical properties and quality control standards.

Except as specifically provided herein, Mar-flex makes no warranty, express, implied or oral including but not limited to any warranty or merchantability, fitness for a particular purpose, usage of trade, course of dealing or course of performance in connection with this agreement. In no event shall Mar-flex be liable on any such warranty with respect to the products. Mar-flex shall not be liable for incidental or consequential damages including, but not limited to damages of the structure, its replacement, contents or personal injury. Some states do not allow limitations on how long an implied warranty lasts or allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

HEALTH AND SAFETY INFORMATION IS GIVEN IN THE MATERIAL SAFETY DATA SHEET AND THE PRODUCT DATA SHEET AVAILABLE FOR THIS PRODUCT. THESE SHOULD BE READ AND UNDERSTOOD BEFORE USING THIS PRODUCT.

Mar-flex Waterproofing and Building Products
PO Box 8256
Carlisle, OH 45005
(800) 498-1411 | (513) 422-7285
Fax – (513) 422-7282
E-mail: info@mar-flex.com
Web-site: www.mar-flex.com