



## Exterior Below-Grade Residential Waterproofing Accessories

# Mar-flex Drain & Dry Board

### **PRODUCT DESCRIPTION:**

Drain & Dry Board with ECOSE Technology is a semi-rigid board made from inorganic glass fibers, bonded with a revolutionary new binder chemistry that does not contain phenol, formaldehyde, acrylics or artificial colors.

### **PURPOSE:**

Drain & Dry Board, when installed from the footing to the sill plate, addresses a major source of energy consumption; the conditioned but un-insulated basement and lower levels of a home.

Drain & Dry Board acts as a drainage medium to channel ground moisture away from the structures foundation and into the buildings drain tile system.

The board also protects the Marflex waterproofing membrane, especially during backfilling or other construction activity.

### **ADVANTAGES:**

- Available in thermal values of R-3.1, R -5 and R-10.0
- Meets the needs of builders, energy conscious homebuyers and/or local building codes
- Combines high R-value, drainage and protection into one product
- Good drainage
- Easy to handle
- Easy to install
- Can be used in any geographical area

### **LEEDS DATA:**

Drain & Dry with ECOSE technology is considered a GREEN product and can be used toward LEEDS building credits.

### **SPECIFICATIONS:**

- Compressive Strength – ASTM C-165  
¾" - 46.8 psf; 1<sup>3</sup>/<sub>16</sub>" - 22.72 psf; 2<sup>3</sup>/<sub>8</sub>" - 30.72 psf
- Drainage Capacity - (K97) ASTM D-4716-87  
¾" - Up to 65 gal/hr/lin.ft.; 1<sup>3</sup>/<sub>16</sub>" - Up to 125 gal/hr/lin.ft.; 2<sup>3</sup>/<sub>8</sub>"  
Up to 190 gal/hr/lin.ft.
- Density – (All 4.0 nominal)
- ¾" - 4.39 pcf; 1<sup>3</sup>/<sub>16</sub>" - 3.8 pcf; 2<sup>3</sup>/<sub>8</sub>" - 4.2 pcf
- Flame spread of 25 and smoke developed of 50.

### **PACKAGING:**

¾" x 3' x 4' - (18 pcs/bundle); 1<sup>3</sup>/<sub>16</sub>" x 3' x 4' - (12 pcs/bundle);  
2<sup>3</sup>/<sub>8</sub>" x 3' x 4' - (6 pcs/bundle)

### **COVERAGE:**

¾" - 216 sq.ft./bundle; 1<sup>3</sup>/<sub>16</sub>" - 144 sq.ft./bundle; 2<sup>3</sup>/<sub>8</sub>" - 72 sq.ft./bundle

### **PREP/APPLICATION:**

Apply one of the Marflex waterproofing membranes following the current installation instructions.

While the membrane is still tacky, install the Drain & Dry Board over the sprayed sections of the wall. The boards should be placed side by side, extending from the top of the footers to finished grade. If boards are stacked, maintain a factory-equivalent edge at all seams to ensure proper fit and drainage channel alignment.

For good adherence, apply uniform pressure to the board throughout the surface area, not just the edges and corners. If needed, secure panels to the wall using powder actuated mechanical fasteners. Install top fasteners within the top 4" (102 mm) of each panel.

If the board overlaps the membrane once you have reached the grade line, a utility knife or similar tool can be used to cut the boards to the correct height.

### **BACKFILLING/DRAINAGE<sup>1</sup>:**

Backfilling should begin no sooner than 24 hours after the installation of the board, but must be backfilled within 15 days.

#57 Gravel or equivalent must be no less than 2' high at the base of the foundation and 1' in depth away from the foundation walls.

Adequate interior and exterior foundation drainage at the base of the foundation walls or across any floors must be properly installed and working. Gutters and downspouts must be installed and functioning properly.

Adequate drainage in landscaping beds adjacent to the foundation must be installed.

Final grade must not extend above the waterproofing system and must slope away from the foundation at a minimum of ½" per foot for the first 12' from the structure.

### **CLEAN UP:**

Disposal methods must be in compliance with all federal, state and local laws and regulations.

### **PRODUCT HANDLING/STORAGE:**

- Maintain good housekeeping
- Keep board dry

### **WARNING/DANGERS:**

- Use safety glasses/Dust Mask
- Protect from flame and other high heat sources

### **Product Only Warranty:**

We warrant the product to be of good quality and manufactured to meet published physical properties and quality control standards.

<sup>7</sup>See written warranty for conditions, exclusions and limitations on drainage



**WATERPROOFING &  
BUILDING PRODUCTS**



**RESIDENTIAL  
PRODUCT**

*Exterior Below-Grade Residential Waterproofing Accessories*

## **Mar-flex Drain & Dry Board**

Except as specifically provided herein, Mar-flex makes no warranty, express, implied or oral including but not limited to any warranty or merchantability, fitness for a particular purpose, usage of trade, course of dealing or course of performance in connection with this agreement. In no event shall Mar-flex be liable on any such warranty with respect to the product. Mar-flex shall not be liable for incidental or consequential damages including, but not limited to damages of the structure, its replacement, contents or personal injury. Some states do not allow limitations on how long an implied warranty lasts or allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

**HEALTH AND SAFETY INFORMATION IS GIVEN IN THE SAFETY DATA SHEET AVAILABLE FOR THIS PRODUCT. THE MATERIAL SAFETY DATA SHEET SHOULD BE READ AND UNDERSTOOD BEFORE USING THIS PRODUCT.**

Marflex Waterproofing & Building Products  
500 Business Pkwy Carlisle, Oh 45005  
(800) 498-1411 | (513) 422-7285 | Fax (513) 422-7282  
E-mail: [info@mar-flex.com](mailto:info@mar-flex.com)  
Web-site: [www.mar-flex.com](http://www.mar-flex.com)

Rev. 1.2017

**Order Today! Contact Mar-flex for the dealer nearest you.** 800-498-1411 | 513-422-7285 | Fax 513-422-7282 | [Mar-flex.com](http://Mar-flex.com)

©2015 Mar-flex Waterproofing & Building Products. All rights reserved.